



8115 Loop 540, Beasley, TX 77417  
Toll Free: 1-855-FINORIC (1-855-346-6742)  
Email: info@finoric.com • www.finoric.com

## HPHT-W Lube™

### General Description:

HPHT-W Lube™ is a high-tech lubricant specifically developed for applications in aqueous environments where normal lubricants degrade into soaps which cause solids and foaming issues. HPHT-W Lube™ is chemically designed to have a high affinity for metal surfaces. This guarantees that the lubricant will be concentrated exactly where it is needed. HPHT-W Lube™ eliminates torque and drag, prevents differential sticking, and protects the system from corrosion, and does not react even under high-temperature and high-pressure conditions.

### Typical Physical Properties:

Form, @ 70°F	Liquid
Density, (lbs/Gal)	7.73
Coefficient of Friction	0.06
Flash Point, °F (TCC)	>200
Pour Point, °F	< 30
pH, (5% in 3:1 IPA / water)	5.5 - 7.5
Solubility	
Water and Brine	Dispersible
Xylene and Mineral Oil	Soluble

### Compatibility:

Compatible with known drilling and coiled tubing fluids and additives, and produced waters. A compatibility test is always recommended.

### Environment:

Not hazardous to the environment.

### Typical Dosage:

The extreme efficiency of this product allows for low use levels.

In drilling applications, for a typical 800- 1000 bbl system, add 2 bbl slowly (one bbl per hour). Maintain the system as needed while drilling. Always add the product s-l-o-w-l-y into the suction pit as close to the suction line as possible. HPHT-W Lube™ is an oil soluble product and will not mix readily with the drilling fluid, but it contains a surfactant package to ensure good dispersion.

Similarly for Coiled Tubing, typically used at 0.3% to 2% on a continuous basis or spotted as required in stuck-pipe situations.

### Temperature Limitations:

Can be used across a wide temperature range, no lower or upper temperature limitations on performance. Has been effectively used up to BHT of 400 F. Stable up to 450 F.

### Packaging:

330 ga one way totes, 275 ga one way totes, 55 ga drums and bulk tank trucks

### Availability:



8115 Loop 540, Beasley, TX 77417  
Toll Free: 1-855-FINORIC (1-855-346-6742)  
Email: [info@finoric.com](mailto:info@finoric.com) • [www.finoric.com](http://www.finoric.com)

---

Pleasanton, TX; Beasley, TX; OKC, OK; Williston, ND; Waskom, TX and Midland, TX

**DoT Classification:**

Not Regulated